
SW-3061

Type Standard solar module **12V** *state 2006*



SW-3061

Product description

SunWare solar modules are designed and tested specifically for use in marine and salt water.
The modules are completely maintenance-free, durable, and weatherproof.
Even under extreme exposure to UV rays whether in the Caribbean, the Mediterranean, or the North Sea SunWare solar modules are always a reliable partner.
Their distinctive feature:
all 12V standard solar modules are designed with 40 cells. Consequently, SunWare solar modules can be fitted without rear ventilation.
Thus, any voltage drop due to high outside temperatures is compensated by the 4 additionally integrated cells to enable a full recharge of the battery.

The back of the module is completely flat so that it can be screwed or glued flush to the deck. SunWare standard solar modules should always be fitted to a firm, inflexible surface.
The modules can be fitted flat to deck surfaces with a curving of up to 3%.
Due to the extremely flat module structure, the module only adds 3mm, and 15mm at the cable outlet.
The 3m PU sheathed cable is robust, UV resistant and weatherproof.
To reduce the risk of slipping in wet conditions, the module surface is slightly structured.
Within the scope of constant quality control, each individual module is tested and calibrated prior to delivery.

SunWare Solartechnik GmbH & Co KG
Düsseldorfer Straße 80
D-47239 Duisburg-Rumeln

TEL +49 (0)2151 406045
FAX +49 (0)2151 40165

MAIL info@sunware.de
WEB www.sunware.de

SW-3061

Technical features


Technical features	Value	Unit
P max	**12**	**Wattpeak**
I max	0,55	Ampère
U oc	24,6	Volt
I sc	0,6	Ampère
Qty. of cells	40	pieces
Cell size	35 x 52	mm
Laminate	ETFE/TPU/stainless steel	
Length	467	mm
Width	249	mm
Drill hole	4 pieces, D=5,5	mm
Batt. System	12	Volt
Carrier plate	VA, pulver coated	
Connecting box	completely sealed	
Cabel	2 x 1,5	qmm
	red = "+", blue = "-"	
Colour	white	
Packaging	indiv. packed	
Weight netto	1,2	kg
Weight brutto	1,7	kg

Technical changes reserved.


Installation

- simple installation using adhesive, screws, or the SunWare mounting clips
- modules must be installed such as to prevent vibration
- when installed to a firm, inflexible surface, the modules can be walked on with boat shoes
- modules have 3% flexibility usually sufficient for curved deck surfaces on board


Field of application



Electrical characteristic



Dimensioning



SunWare Solartechnik GmbH & Co KG
Düsseldorfer Straße 80
D-47239 Duisburg-Rumeln

TEL +49 (0)2151 406045
FAX +49 (0)2151 40165

MAIL info@sunware.de
WEB www.sunware.de